

## QUALITY ASSURANCE SYSTEM – PRODUCT DATA SHEET

<u>Product reference N°</u>	CS2	Issue N° 5
<u>Product Description</u>	0/4 All-in Crushed Fine Basalt Aggregate	
<u>Trade Description</u>	Basalt Dust	

### Specification Details

Aggregate for Bituminous Mixtures and Surface Treatments to BS EN 13043:2002 & PD6682-2, Table 5, Category G<sub>a</sub>85/G<sub>ic</sub>20 EN13043:

<u>BS Sieve Size</u>	<u>Grading Limits %</u>	<u>Typical Stock Result %</u>
8.0mm	100	-
6.3mm	98 to 100	100
4.0mm	89 to 99	94
2.0mm	45 to 85	65
1.0mm	-	38
0.063mm	9 to 15	12

### Comments

Typical Moisture Content = 2.2%

### Recommendations of use

Coated Grit to **BS4987-1:2005**, see Product Data Sheet No. **MC1**.

Suitable for use in the majority of Bituminous and Concrete products.

For all other applications consult The **Quarry Laboratory**.

Not suitable without blending with Pit Sand for use in **30%** Asphalt, requiring the application of Pre-coated chippings.

Issued by:

Ian Timberlake



Date Issued: 05/09/06