

**QUALITY ASSURANCE SYSTEM – PRODUCT DATA SHEET**

<b><u>Product reference N°</u></b>	<b>CS3</b>	<b>Issue N° 6</b>
<b><u>Product Description</u></b>	<b>Proprietary Graded 5mm Coarse Basalt Aggregate.</b>	
<b><u>Trade Description:</u></b>	<b>5mm Basalt Chippings</b>	
<b><u>Source</u></b>	<b>Without prior notice, only available from bins</b>	

**Specification Details**

BS EN 13043:2002 and PD 6682-2:2003, Table 3, Grading Category G<sub>c</sub>80/20 (as no 5mm specification available):

<u>Sieve Size</u>	<u>Grading Limits %</u>	<u>Typical Result %</u>
14.0mm	100	100
10.0mm	98 to 100	100
6.3mm	80 to 99	98
4.0mm	-	27
2.8mm	-	9
2.0mm	0 to 20	5
1.0mm	0 to 5	2

**Recommendations of use**

Suitable for use in Bituminous Mixtures and Surface Treatments for roads and other paved areas, requiring a minimum aggregate Polished Stone Value of **PSV<sub>55</sub>**

For use in Concrete requiring aggregates complying with BS EN 12620:2002.

Blending with 2/6.3 Moons Hill Basalt coarse aggregate.

Racking-in Surface Treatments.

Issued by:

Ian Timberlake



Date Issued: 05/09/06